[redacted]

Klassifikation gemäss den
VKF-Prüfbestimmungen Hagelregister

Gokin Solar (HongKong) Company Limited
Lockhart Road 54-62
999077 Wanchai, HK
China

Guangzhou Gokin Solar Technology Co Ltd
510800 Guangdong
China

121 - Dach - Photovoltaik Module

GK-1-72HTBD-xxxM; GK-1-54HTBD-xxxM; GK-4-66HTBD-xxxM; GK-4-54HTBD-xxxM; GK-4-48HTBD-xxxM; GK-3-72HGBD-xxxM; GK-3-54HGBD-xxxM; GK-3-54HGDb-xxxM; GK-5-60HGBD-xxxM; GK-5-60HGDb-xxxM; GK-5-54HGBD-xxxM; GK-5-54HGDb-xxxM
Glas-Glas Photovoltaikmodul.
Frontglas vorgespannt/teilvorgespannt, Stärke = 2,0 mm.
Rückseitenglas vorgespannt/teilvorgespannt, Stärke = 2,0 mm.
Umlaufender Rahmen aus Aluminium, Höhe = 30 mm.
xxx bezeichnet die Leistung in Wp.
Die Anerkennung bezieht sich auf den solaren Teil und alle erhältlichen Leistungsklassen.

-: Bestätigung Hersteller '20251203' (3. Dezember 2025)

Beschluss B Beschluss für die Zuordnung von nach IEC- und ISO-Normen geprüften solaren Elementen zu einer Hagelwiderstandsklasse, Version 1.04 vom 01.11.2016

Hagelwiderstand Funktionalität HW 3

31.12.2030
22.12.2025

Vereinigung Kantonaler Feuerversicherungen

Die Funktionalität ist der minimale Hagelwiderstand von den Bauteilfunktionen:

Lichtdurchlässigkeit	HW --	Mechanik	HW --
Lichtabschirmung	HW --	Wasserdichtheit	HW --