


Mechanical Parameters

Cell Type	GBC
No. of cells	108 6×18
Glass	3.2 mm tempered glass
Frame	Black anodized aluminum
Output Cables	TüV 1×4mm², (+)300mm, (-)200mm or Customized Length
Weight	21.4kg (47.18lbs)
Dimension	1800×1134×30mm
Connector	Staubli Electrical Connectors AG – MC4 EVO2 Series PV-KST4-EVO2A/xy, PV-KBT4-EVO2A/xy
Packaging	36 pcs per pallet 216 pcs per 20' GP, 864 pcs per 40' HC

Engi



* L:±2mm W:±2mm Unit:mm

Electrical Characteristics STC Test)

Module Type	GK-3-54HGF-495M		GK-3-54HGF-500M		GK-3-54HGF-505M		GK-3-54HGF-510M	
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax/W)	495	377	500	381	505	385	510	389
Open-circuit Voltage (Voc/V)	40.74	38.28	40.84	38.38	40.94	38.48	41.04	38.58
Maximum Power Voltage (Vmp/V)	35.44	32.28	35.54	32.38	35.64	32.48	35.74	32.58
Short-circuit Current (Isc/A)	15.08	12.30	15.18	12.36	15.28	12.42	15.38	12.48
Maximum Power Current (Imp/A)	13.98	11.69	14.08	11.78	14.18	11.87	14.28	11.96
Module Efficiency (%)	**24.3**		**24.5**		**24.7**		**25.0**	

Temperature Ratings STC)

Temperature Coefficient of Isc	+ 0.05%/
Temperature Coefficient of Voc	- 0.22%/
Temperature Coefficient of Pmax	- 0.26%/

Gokin

GK-3-54HGF-BF-SG-CEC

© Gokin Solar Co., Ltd. All rights reserved.

Note: Please read the safety and installation manual before using the product. We reserve the right of final interpretation. The specifications in this datasheet are subject to change without notice.

Production Base: No.1 Hejin Avenue, Automotive Industry Base, Huadu District Guangzhou City, Guangdong Province

www.gokinsolar.com gk@gokinsolar.com

*Made in China