Gokin

GBC Module with Single Glass
Full-screen Mystic Black

495-510W

- Full-screen
- High Efficiency
- Anti-fire
- Anti-covering

25 Years Product Warranty

30 Years Linear Power Warranty

Module Efficiency up to

≤**1%** First-year Degradation

≤**0.35%** Annual Degradation

TÜVRheinland CERTIFIED www.tuv.com

CE

Mechanical Parameters

Cell Type	GBC
No. of cells	108 6×18
Glass	3.2 mm tempered glass
Frame	Black anodized aluminum
Output Cables	TüV 1×4mm2, (+)300mm, (-)200mm or Customized Length
Weight	21.4kg (47.18lbs)
Dimension	1800×1134×30mm
Connector	Staubli Electrical Connectors AG – MC4 EVO2 Series PV-KST4-EVO2A/xy, PV-KBT4-EVO2A/xy
Packaging	36 pcs per pallet 216 pcs per 20’ GP, 864 pcs per 40’ HC

Engineering Drawings

* L:±2mm W:±2mm Unit:mm

Electrical Characteristics STC Test)

Module Type	
Testing Condition	
Maximum Power (Pmax/W)	
Open-circuit Voltage (Voc/V)	
Maximum Power Voltage (Vmp/V)	
Short-circuit Current (Isc/A)	
Maximum Power Current (Imp/A)	
Module Efficiency (%)	

Please read the safety and installation manual before using the product. We reserve the right of final interpretation. The speci8 þ [illegible]